



Technical data

- Installation cable acc. to DIN VDE 0815
- **Temperature range**
during operation -5°C to +50°C
fixed installation -30°C to +70°C
- **Loop resistance** at 20°C
0,6 mm - max. 130 Ohm/km
0,8 mm - max. 73,2 Ohm/km
- **Operating peak voltage**
(not for purposes of high current and power installation)
0,6 mm - 300 V
0,8 mm - 300³⁾ V
- **Test voltage**
core/core U eff. 800 V
core/screen 800 V
- **Insulation resistance**
min. 100 MOhm x km
- **Mutual capacitance** at 800 Hz
max. 100¹⁾ nF/km
- **Capacitance unbalances** at 800 Hz
k- max. 300²⁾ pF/100 m
- **Line attenuation** at 800 Hz
0,6 mm - 1,7 dB/km
0,8 mm - 1,1 dB/km
- **Minimum bending radius**
to DIN VDE 0891 part 5
during delivery 7,5x cable Ø
single bending without tension
5x cable Ø
repeated bending under tension
7,5x cable Ø
- **Radiation resistance**
up to 80x10⁶ cJ/kg (up to 80 Mrad)
- **Caloric load values**
see Technical Informations

Cable structure

- Bare copper-conductor, single-wire
- Core insulation of PVC, compound type Y11 to DIN VDE 0207 part 4
- Core and pair identification to DIN VDE 0815
- Cores twisted to pairs and the pairs are stranded in layers
- Foil wrapping
- Electrostatic screen (St) of plastic coated aluminium foil and drain wire
- Outer sheath of PVC, flame retardant, compound type YM1 to DIN VDE 0207 part 5
- Sheath colour grey

Properties

- PVC self-extinguishing and flame retardant acc. to DIN VDE 0482-332-1-2, DIN EN 60332-1-2, IEC 60332-1 (equivalent DIN VDE 0472 part 804 test method B)
- The materials used in manufacture are cadmium-free and contain no silicone and free from substances harmful to the wetting properties of lacquers

Note

- ¹⁾ This value may be extended by 20% with a make-up to 4 pairs.
- ²⁾ 20% of the values, but one value up to 500 pF is allowed.
- ³⁾ Short time operation (6 s/min) up to 600 V permitted.
- 2-paired cables:
cores are stranded to a star quad.

Application

This cable type with electrostatic screening (St) protects the transmission circuits against external electrical interferences. Installation cables laid up in pairs are preferably used for telecommunications installations, in dry and damp premises, and in or under plaster, in the open air for fixed installation. These cables are suitable for telephone stations and sub-extensions, for signal and data transmission. Telephone-Installation cables are not allowed for purposes of high current and power installation.

CE= The product is conformed with the EC Low-Voltage Directive 2006/95/EC.

Part no.	No.pairs x cross-sec. mm	Outer Ø approx. mm	Cop. weight kg / km	Weight approx. kg / km		Part no.	No.pairs x cross-sec. mm	Outer Ø approx. mm	Cop. weight kg / km	Weight approx. kg / km	
33001	2 x 2 x 0,6	5,0	13,0	40,0	-	33018	2 x 2 x 0,8	7,0	21,0	60,0	-
33002	3 x 2 x 0,6	6,3	18,0	50,0	-	33019	3 x 2 x 0,8	8,5	31,0	80,0	-
33003	4 x 2 x 0,6	6,5	24,0	60,0	-	33020	4 x 2 x 0,8	9,0	41,0	100,0	-
33004	5 x 2 x 0,6	7,2	30,0	70,0	-	33021	5 x 2 x 0,8	9,5	52,0	120,0	-
33005	6 x 2 x 0,6	7,5	35,0	80,0	-	33022	6 x 2 x 0,8	11,0	62,0	140,0	-
33006	8 x 2 x 0,6	8,0	46,0	90,0	-	33023	8 x 2 x 0,8	11,5	82,0	170,0	-
33007	10 x 2 x 0,6	10,0	58,0	110,0	-	33024	10 x 2 x 0,8	13,2	102,0	220,0	-
33008	12 x 2 x 0,6	10,2	71,0	130,0	-	33025	12 x 2 x 0,8	14,2	123,0	250,0	-
33009	16 x 2 x 0,6	11,0	93,0	160,0	-	33026	16 x 2 x 0,8	16,0	164,0	320,0	-
33010	20 x 2 x 0,6	12,0	116,0	190,0	-	33027	20 x 2 x 0,8	17,0	204,0	380,0	-
33011	24 x 2 x 0,6	13,0	139,0	220,0	-	33028	24 x 2 x 0,8	19,0	244,0	460,0	-
33012	30 x 2 x 0,6	14,0	172,0	280,0	-	33029	30 x 2 x 0,8	20,8	304,0	560,0	-
33013	40 x 2 x 0,6	15,0	220,0	350,0	-	33030	40 x 2 x 0,8	23,0	405,0	710,0	-
33014	50 x 2 x 0,6	17,0	286,0	430,0	-	33031	50 x 2 x 0,8	26,0	505,0	900,0	-
33015	60 x 2 x 0,6	19,0	342,0	500,0	-	33032	60 x 2 x 0,8	28,0	606,0	1050,0	-
33016	80 x 2 x 0,6	21,0	455,0	640,0	-	33033	80 x 2 x 0,8	31,5	807,0	1400,0	-
33017	100 x 2 x 0,6	24,0	568,0	850,0	-	33034	100 x 2 x 0,8	33,0	1008,0	1750,0	-

Dimensions and specifications may be changed without prior notice. (RP01)