


# JZ-600

flexible, number coded, 0,6/1 kV, meter marking



## Technical data

- Special PVC control cable adapted to DIN VDE 0262 and DIN VDE 0285-525-2-51 / DIN EN 50525-2-51, with insulation wall thickness for 1 kV
- **Temperature range**  
flexing -15°C to +80°C  
fixed installation -40°C to +80°C
- **Nominal voltage**  
U<sub>0</sub>/U 0,6/1 kV
- **Test voltage**  
4000 V
- **Breakdown voltage**  
min. 8000 V
- **Insulation resistance**  
min. 20 MOhm x km
- **Minimum bending radius**  
flexing 7,5x cable Ø  
fixed installation 4x cable Ø
- **Radiation resistance**  
up to 80x10<sup>6</sup> cJ/kg (up to 80 Mrad)

## Cable structure

- Bare copper conductor, to DIN VDE 0295 cl.5, fine wire, BS 6360 cl.5, IEC 60228 cl.5
- Core insulation of special PVC compound type TI2 to DIN VDE 0207-363-3 / DIN EN 50363-3
- Core identification to DIN VDE 0293  
black cores with continuous white numbering
- GN-YE conductor, 3 cores and above in the outer layer
- Cores stranded in layers with optimal lay length
- Outer sheath of special PVC compound type TM2 to DIN VDE 0207-363-4-1/DIN EN 50363-4-1
- Sheath colour: black (RAL 9005)
- With meter marking

## Properties

- Extensively oil resistant, oil-/chemical resistance see "Technical Informations"
- The materials used during manufacturing are cadmium-free, contain no silicone and are free from substances harmful to the wetting properties of lacquers
- UV resistant

## Tests

- PVC self-extinguishing and flame retardant acc. to DIN VDE 0482-332-1-2, DIN EN 60332-1-2, IEC 60332-1-2 (equivalent DIN VDE 0472 part 804 test method B)

## Note

- G = with GN-YE conductor  
x = without GN-YE conductor (OZ)
- AWG sizes are approximate equivalent values. The actual cross section is in mm<sup>2</sup>.
- Screened analogue type:  
**JZ-600-Y-CY**

## Application

Wiring cable for measuring and controlling purposes in tool machinery, conveyor belts and production lines, for plant installations, air conditioning and in steel production plants and rolling mills. Suitable for installation for flexible use for medium mechanical stresses with free movement without tensile stress or forced movements in dry, moist and wet rooms as well as outside (fixed installation). Is not suitable to be used as direct burria (suitable from an outer diameter of 18,0 mm for direct burial) or as underwater cable. The cores have been numbered in such a way that the numbers are easily identifiable, even if the cable has only been stripped back a few cm. The core numbers have been underlined to avoid confusion. The earth core is located in the outer layer. The black, special PVC outer sheath is resistant to the ultra violet radiation. Mainly used in South-European, Eastern and Arabian countries.

CE = Product conforms with Low-Voltage Directive 2014/35/EU.

Part no.	No. cores x cross-sec. mm <sup>2</sup>	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
10550	2 x 0,5	6,2	9,6	56,0	20
10551	3 G 0,5	6,5	14,0	68,0	20
10552	3 x 0,5	6,5	14,0	68,0	20
10553	4 G 0,5	7,1	19,0	100,0	20
10554	4 x 0,5	7,1	19,0	100,0	20
10555	5 G 0,5	7,9	24,0	117,0	20
10556	5 x 0,5	7,9	24,0	117,0	20
10557	6 G 0,5	8,5	29,0	126,0	20
10558	7 G 0,5	8,5	34,0	138,0	20
10559	7 x 0,5	8,5	34,0	138,0	20
10560	8 G 0,5	9,5	38,0	150,0	20
10561	8 x 0,5	9,5	38,0	150,0	20
10562	10 G 0,5	10,8	48,0	176,0	20
10563	12 G 0,5	11,3	58,0	200,0	20
10564	12 x 0,5	11,3	58,0	200,0	20
10565	14 G 0,5	12,1	67,0	230,0	20

Part no.	No. cores x cross-sec. mm <sup>2</sup>	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
10566	16 G 0,5	12,7	76,0	250,0	20
10567	18 G 0,5	13,5	86,0	276,0	20
10568	20 G 0,5	14,2	96,0	293,0	20
10569	21 G 0,5	14,2	96,0	305,0	20
10570	25 G 0,5	15,8	120,0	335,0	20
10571	30 G 0,5	16,9	144,0	348,0	20
10572	32 G 0,5	18,5	154,0	355,0	20
10573	34 G 0,5	18,7	163,0	520,0	20
10574	40 G 0,5	20,1	192,0	590,0	20
10575	42 G 0,5	20,1	202,0	595,0	20
10576	50 G 0,5	21,7	240,0	715,0	20
10577	52 G 0,5	21,7	252,0	740,0	20
10578	61 G 0,5	23,1	293,0	840,0	20
10579	65 G 0,5	24,6	312,0	880,0	20
10580	80 G 0,5	26,7	384,0	960,0	20
10581	100 G 0,5	29,6	480,0	1050,0	20

Continuation ▶

# JZ-600

flexible, number coded, 0,6/1 kV, meter marking



Part no.	No. cores x cross-sec. mm <sup>2</sup>	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
10582	2 x 0,75	6,7	14,0	66,0	19
10583	3 G 0,75	7,1	22,0	74,0	19
10584	3 x 0,75	7,1	22,0	74,0	19
10585	4 G 0,75	7,7	29,0	126,0	19
10586	4 x 0,75	7,7	29,0	126,0	19
10587	5 G 0,75	8,5	36,0	140,0	19
10588	5 x 0,75	8,5	36,0	140,0	19
10589	6 G 0,75	9,5	43,0	170,0	19
10590	6 x 0,75	9,5	43,0	170,0	19
10591	7 G 0,75	9,5	50,0	190,0	19
10592	7 x 0,75	9,5	50,0	190,0	19
10593	8 G 0,75	10,5	58,0	212,0	19
10594	8 x 0,75	10,5	58,0	212,0	19
10595	9 G 0,75	11,8	65,0	227,0	19
10596	10 G 0,75	12,0	72,0	238,0	19
10597	12 G 0,75	12,6	86,0	257,0	19
10598	12 x 0,75	12,6	86,0	257,0	19
10599	14 G 0,75	13,2	101,0	286,0	19
10600	15 G 0,75	14,0	108,0	319,0	19
10601	18 G 0,75	14,8	130,0	362,0	19
10602	20 G 0,75	15,7	144,0	394,0	19
10603	21 G 0,75	15,7	151,0	422,0	19
10604	25 G 0,75	17,5	180,0	486,0	19
10605	32 G 0,75	19,3	230,0	595,0	19
10606	34 G 0,75	20,3	245,0	638,0	19
10607	37 G 0,75	20,3	260,0	696,0	19
10608	40 G 0,75	21,8	288,0	726,0	19
10609	41 G 0,75	22,0	296,0	750,0	19
10610	42 G 0,75	22,0	302,0	770,0	19
10611	50 G 0,75	24,2	360,0	895,0	19
10612	61 G 0,75	25,8	439,0	1070,0	19
10613	65 G 0,75	27,4	468,0	1110,0	19
10614	80 G 0,75	29,5	576,0	1500,0	19
10615	100 G 0,75	32,7	720,0	1889,0	19
10616	2 x 1	7,0	19,2	80,0	18
10617	3 G 1	7,4	29,0	96,0	18
10618	3 x 1	7,4	29,0	96,0	18
10619	4 G 1	8,3	38,0	100,0	18
10620	4 x 1	8,3	38,0	100,0	18
10621	5 G 1	9,2	48,0	130,0	18
10622	5 x 1	9,2	48,0	130,0	18
10623	6 G 1	9,9	58,0	150,0	18
10624	7 G 1	9,9	67,0	170,0	18
10625	7 x 1	9,9	67,0	170,0	18
10626	8 G 1	11,0	77,0	230,0	18
10627	9 G 1	12,6	86,0	250,0	18
10628	10 G 1	12,8	96,0	270,0	18
10629	10 x 1	12,8	96,0	270,0	18
10630	12 G 1	13,2	115,0	290,0	18
10631	12 x 1	13,2	115,0	290,0	18
10632	14 G 1	14,1	134,0	320,0	18
10633	16 G 1	14,8	154,0	360,0	18
10634	18 G 1	15,7	173,0	405,0	18
10635	18 x 1	15,7	173,0	405,0	18
10636	20 G 1	16,7	192,0	450,0	18
10637	20 x 1	16,7	192,0	480,0	18
10638	21 G 1	16,7	205,0	510,0	18
10639	24 G 1	18,6	236,0	550,0	18
10640	25 G 1	18,6	240,0	570,0	18
10641	25 x 1	18,6	240,0	570,0	18
10642	26 G 1	19,0	252,0	590,0	18
10643	30 x 1	19,9	308,0	650,0	18
10644	34 G 1	21,5	326,0	750,0	18
10645	36 G 1	21,5	346,0	790,0	18
10646	40 G 1	23,4	384,0	850,0	18
10647	40 x 1	23,4	384,0	850,0	18
10648	41 G 1	23,4	394,0	890,0	18
10649	42 G 1	23,4	403,0	900,0	18
10650	50 G 1	25,7	480,0	1100,0	18
10651	56 G 1	26,4	538,0	1190,0	18
10652	61 G 1	27,3	586,0	1266,0	18
10653	65 G 1	29,0	628,0	1560,0	18
10654	80 G 1	31,4	786,0	1810,0	18
10655	100 G 1	34,8	960,0	1950,0	18
10656	2 x 1,5	8,2	29,0	95,0	16
10657	3 G 1,5	8,7	43,0	112,0	16
10658	3 x 1,5	8,7	43,0	112,0	16
10659	4 G 1,5	9,7	58,0	139,0	16
10660	4 x 1,5	9,7	58,0	139,0	16
10661	5 G 1,5	10,7	72,0	170,0	16
10662	5 x 1,5	10,7	72,0	170,0	16
10663	6 G 1,5	11,6	86,0	190,0	16
10664	7 G 1,5	11,6	101,0	225,0	16
10665	7 x 1,5	11,6	101,0	225,0	16

Part no.	No. cores x cross-sec. mm <sup>2</sup>	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
10666	8 G 1,5	13,1	115,0	250,0	16
10667	9 G 1,5	14,8	130,0	280,0	16
10668	10 G 1,5	15,0	144,0	300,0	16
10669	11 G 1,5	15,7	158,0	330,0	16
10670	12 G 1,5	15,7	173,0	370,0	16
10671	12 x 1,5	15,7	173,0	370,0	16
10672	14 G 1,5	16,7	202,0	400,0	16
10673	16 G 1,5	17,5	230,0	450,0	16
10674	18 G 1,5	18,6	259,0	520,0	16
10675	19 G 1,5	18,8	279,0	550,0	16
10676	20 G 1,5	19,8	288,0	600,0	16
10677	21 G 1,5	19,8	302,0	600,0	16
10678	25 G 1,5	22,2	360,0	730,0	16
10679	32 G 1,5	24,5	461,0	880,0	16
10680	34 G 1,5	25,6	490,0	950,0	16
10681	40 G 1,5	27,8	576,0	990,0	16
10682	42 G 1,5	27,8	605,0	1120,0	16
10683	50 G 1,5	30,5	720,0	1400,0	16
10684	56 G 1,5	31,5	806,0	1530,0	16
10685	61 G 1,5	32,6	878,0	1700,0	16
10686	65 G 1,5	34,6	936,0	1900,0	16
10687	80 G 1,5	37,4	1152,0	2300,0	16
10688	100 G 1,5	41,6	1440,0	2700,0	16
10689	2 x 2,5	9,6	48,0	160,0	14
10690	3 G 2,5	10,2	72,0	175,0	14
10691	3 x 2,5	10,2	72,0	175,0	14
10692	4 G 2,5	11,3	96,0	203,0	14
10693	4 x 2,5	11,3	96,0	203,0	14
10694	5 G 2,5	12,5	120,0	251,0	14
10695	5 x 2,5	12,5	120,0	251,0	14
10696	7 G 2,5	13,8	168,0	330,0	14
10697	7 x 2,5	13,8	168,0	330,0	14
10698	8 G 2,5	15,3	192,0	400,0	14
10699	12 G 2,5	18,6	288,0	553,0	14
10700	14 G 2,5	19,7	336,0	630,0	14
10701	18 G 2,5	22,0	432,0	795,0	14
10702	21 G 2,5	23,4	504,0	930,0	14
10703	25 G 2,5	26,2	600,0	1110,0	14
10704	34 G 2,5	30,4	816,0	1450,0	14
10705	42 G 2,5	33,2	1008,0	1750,0	14
10706	50 G 2,5	36,3	1200,0	2100,0	14
10707	61 G 2,5	38,8	1464,0	2540,0	14
10708	100 G 2,5	49,6	2400,0	3850,0	14
10709	2 x 4	11,0	77,0	180,0	12
10710	3 G 4	11,7	115,0	230,0	12
10711	4 G 4	13,0	154,0	310,0	12
10712	5 G 4	14,3	192,0	410,0	12
10713	7 G 4	15,8	269,0	540,0	12
10714	8 G 4	17,5	307,0	710,0	12
10715	12 G 4	21,5	461,0	860,0	12
10716	3 G 6	13,2	173,0	370,0	10
10717	4 G 6	14,6	230,0	430,0	10
10718	5 G 6	16,2	288,0	650,0	10
10719	7 G 6	18,6	403,0	860,0	10
10720	3 G 10	16,8	288,0	660,0	8
10721	4 G 10	18,6	384,0	790,0	8
10722	5 G 10	20,5	480,0	960,0	8
10723	7 G 10	22,8	672,0	1300,0	8
10724	3 G 16	20,2	461,0	700,0	6
10725	4 G 16	22,4	614,0	1100,0	6
10726	5 G 16	25,0	768,0	1600,0	6
10727	7 G 16	27,4	1075,0	1890,0	6
10728	3 G 25	24,8	720,0	1450,0	4
10729	4 G 25	27,4	960,0	1600,0	4
10730	5 G 25	30,5	1200,0	2050,0	4
10731	7 G 25	33,8	1680,0	2900,0	4
10732	3 G 35	27,4	1008,0	1900,0	2
10733	4 G 35	30,4	1344,0	2400,0	2
10734	5 G 35	33,6	1680,0	2900,0	2
10735	3 G 50	32,3	1440,0	2700,0	1
10736	4 G 50	35,8	1920,0	3400,0	1
10742	5 G 50	39,7	2400,0	4361,0	1
10737	3 G 70	36,6	2016,0	3300,0	2/0
10738	4 G 70	40,7	2688,0	4400,0	2/0
10743	5 G 70	44,9	3360,0	5807,0	2/0
10739	3 G 95	41,9	2736,0	5050,0	3/0
10740	4 G 95	46,6	3648,0	6010,0	3/0
10744	5 G 95	51,7	4560,0	7752,0	3/0
10741	4 G 120	51,6	4608,0	7500,0	4/0
10745	4 G 150	57,4	5760,0	8640,0	300 kcmil
10746	4 G 185	63,2	7104,0	10380,0	350 kcmil

Dimensions and specifications may be changed without prior notice. (RA01)