


Insulating tube SI



SI

Silicone insulating tube for insulating and bundling wires and lines.

Properties

Softener and heavy metal free, physiologically and toxicologically safe with good chemical resistance.

Application

Plant and machine construction Robot construction Automation technology Vehicle construction and shipbuilding Installation technology Control cabinet construction

Material

Silicone rubber acc. to DIN 40628

Colour: natural

Technical data

DIN 40628

Temperature range: °C to +°C

Part No.	Inner Ø mm	Wall thickness mm	Per metres	net EUR/100 metres at acceptance of		
				up to 100	101 - 500	501 - 1000
94741	1,0	0,4	100,0	o. r.	o. r.	o. r.
94742	2,0	0,4	100,0	o. r.	o. r.	o. r.
97203	3,0	0,4	100,0	o. r.	o. r.	o. r.
97426	4,0	0,5	100,0	o. r.	o. r.	o. r.
97427	5,0	0,6	100,0	o. r.	o. r.	o. r.
97757	6,0	0,6	100,0	o. r.	o. r.	o. r.
94743	8,0	0,7	100,0	o. r.	o. r.	o. r.
94744	10,0	0,7	50,0	o. r.	o. r.	o. r.
94745	12,0	0,8	50,0	o. r.	o. r.	o. r.
94746	14,0	0,8	50,0	o. r.	o. r.	o. r.
94747	16,0	0,8	50,0	o. r.	o. r.	o. r.

o. r. = on request